

Product Description:

Premier Infinity flat finish is a paint based on 100% acrylic of pre-composite polymer technology, designed for low traffic areas. It is washable, however on frequently washed surfaces glossier finish is preferable. The high solid content combines the properties of primer and topcoat in one product.

Features:

- Built-in primer
- Superior coverage
- Stain resistant
- Easy to wash
- One-coat color**
- Excellent adhesion
- Spatter resistant
- Quick drying
- Highly durable
- Excellent flow and leveling
- Zero VOC
- Available in white and tint bases

Uses:

Walls, low traffic areas, previously painted or primed drywall and plaster.

⚠️ Precaution:

Dry sanding, flame cutting and/or welding of dry paint film may generate dust and/or fumes. Avoid breathing paint vapors. Always ensure the room is well ventilated when working. Suitable respiratory protective equipment should be used. DO NOT ALLOW PAINT TO FREEZE. MAY CAUSE EYE, NOSE, THROAT AND/OR SKIN IRRITATION. If paint gets in eyes or on skin rinse thoroughly with water. If inhaled move to fresh air. Keep out of reach of children. Harmful if swallowed seek medical attention.

Refer to MSDS for proper health and safety information.

Applicators:

10-13 mm nap roller, nylon or polyester brush, airless sprayer.

Clean-up:

Soap and water.

Storage:

Keep product in a dry and ventilated area between 10-30 °C. Unopened containers may be stored up to 3 years.

Disposal:

Consult your municipality for proper disposal procedures.

Limited Lifetime Warranty:

The performance of the product is backed by a limited lifetime warranty when applied in accordance with label directions to a properly prepared surface. This guarantee is effective for so long as you reside in your home, and is not transferable. In the event of a performance problem, contact 1-866-paint99 (1-866-724-6899). We will at our option, upon proof of purchase provide replacement paint free of charge or refund the full purchase price with a gift card. This warranty excludes (i) labor or cost of labor for the application of any paint, and (ii) any incidental or consequential expenses, losses or damages.

Technical Specifications (25 °C / 77 °F):

Gloss level:

Flat finish
Gloss at 60°: max 5%
Gloss at 85°: max 5%

☺ Drying Time:

Tack free: 1 hr.
To recoat: 3-4 hrs
Full cure: 14 days
If relative humidity is higher than 50%, required time must be doubled.

Spreading Rate per coat:

Covers up to 38-46m² (400-500 ft²) per 3.78 Lt
Excluding losses caused by variations in application methods or surface porosity.

Volatile Organic Compounds (VOCs):

- Zero VOC before the addition of colorant according to ASTM D3960-05. Addition of colorants may introduce VOC.
- No emission detected, when tested by USEPA method#24. (Canadian VOC regulation: < 100 g/L)

Solid by Volume*:

42%

Surface Preparation:

- The surface must be free of dirt, dust, mildew and grease. Clean the surface with a detergent and allow it to dry completely before applying paint or primer.
- Remove any loose or scaling paint by sanding lightly.
- Any holes, cracks or slight imperfections should be filled in with a compound. Glossy surfaces should be dulled.
- New plaster and masonry must be cured before painting.
- For previously painted, uncoated surfaces use Premier Active™ Primer (048-8649-8).
- For unpainted drywall use Premier Active™ Drywall Primer (048-8652-8).
- For severely damaged surface or bleeding stains use Premier Active™ Problem-solving Primer (048-8651-0).
- Although this paint does not require particular primer, it is recommended to apply a base coat on tough stains or on very porous or absorbent surfaces for optimal results.
- For certain deep colors to provide a better hiding use Premier Active™ Tintable Primer (048-8649-8) tinted to the color of top coat.
- Concrete and masonry: No specific primer is required; the first coat will be used as primer.

Application:

- Paint should be applied when air and surface temperature are between 10-32°C (50-89.6°F).
- Do not thin. Stir paint occasionally during application. Tinted paint must be stirred or shaken thoroughly, if stored longer than one week.
- Certain colors may require more than one coat for complete hide.
- Surface may be cleaned after 30 days with a non-abrasive liquid detergent.
- Apply the product by complying with its spreading rate.
- Observe drying time between coats.
- Low temperatures or high humidity will affect drying time.
- Two coats application will provide better durability and appearance.